

AmeriKooler is now offering a convenient, Quick Ship Program to accommodate customers' demand for fast delivery of popular cooler and freezer sizes with Indoor and Outdoor Top Mount Self-Contained and Remote Refrigeration Systems.

INDOOR AND OUTDOOR COOLERS AND FREEZERS

6x6, 6x8, 6x10, 6x12 8x8, 8x10, 8x12

With Floor 7'-7" Height (coolers and freezers) No Floor 7'-2 1/4" Height (coolers)

Your Choice of 30" or 36" Clear Door Opening, Centered

Top Mount Self-contained Units, Indoor and Outdoor 35°F, -10°F Remote Systems, Outdoor 35°F, 0°F, -10°F All Refrigeration with Mounted Components, 208-230/1/60

WARRANTIES

- DOW 50 year thermal warranty on AK-XPS4 insulation
- 15 year original panel warranty
- 1 year limited panel labor warranty
- 1 year original parts warranty
- Refrigeration system components will be covered per original equipment manufacturer's warranty terms and conditions





California Earthquake

Miami-Dade County







and Engineering





New York City

TERMS: Must receive Quick Ship order before 12PM EST to ship within 24 business hours. Orders received in the afternoon count as the next business day. New customers placing their first order require 48 hours for processing with a credit card payment. Shipping lead times are subject to receipt of approved signed drawings, credit approval and standard terms and conditions. Specifications are subject to change without notice due to our continuous product improvements.



SPECIFICATIONS

- 4" thick AK-XPS4 insulation with R-values of R-29 for coolers and R-32 for freezers
- 26 gauge Acrylume® coated corrosion resistant stucco embossed Galvalume on all interior and exterior surfaces
- 30"W x 76"H or 36"W x 76"H flush mounted door
- 2 super cam-rise spring assisted hinges
- Deadbolt keyed handle latch
- Interior safety lock release handle
- Spring actuated door closer
- Digital LED thermometer with on and off pilot light switch
- LED light fixture centered on interior door jamb
- Smooth stainless steel floor finish rated at 700 Lbs. per sq. ft. of uniformly distributed load
- · Freezer door with temperature regulating thermostat and mounted and pre-wired PRV
- · Floorless walk-ins with NSF vinyl screed
- Outdoor walk-in accessories include: rain roof membrane, exterior floor angles and door hood





R-29 for Coolers R-32 for Freezers





