

IMPULSE SERIES

Hot Food Display Cases

FEATURES & BENEFITS

Shelf Configurations: Adjustable shelves can be arranged to hold products of varying size. Both the HFD and the Combo Serve HFD provide a total of 6 selling surfaces and over 6 cubic feet of product space.

Food Timers: 12 multi-selection, adjustable timers 30 minutes - 4 hours (in 30 minute increments).

Flexible Temperature: 6 heating zones can be individually adjusted to the various products being held.

NSF Certified: Quality and safety guaranteed through NSF certification.

Attractive: Xenon light bulbs create a well-lit product display for maximum customer appeal.

Serving Ability: The HFD's roll-out front panel and sliding back doors make cleaning and serving easy. The Combo Serve HFD's swing open front doors and sliding back doors make the case perfect for full and/or self serve applications.

Low Air Flow Dual Fan: Low air flow dual circulation fans help maintain an even and consistent product temperature throughout the case. Fans are standard on all models of Combo-Serve and HFD - Models 5 and 7.

High Product Capacity & Marketability: Fresh, hot food is one of the fastest growing segments for convenience stores. These well-lit, attractive display cases have plenty of room for custom graphics, menu boards or logos that increase aesthetic appeal and "impulse-buy" sales. The HFD is designed for holding unwrapped or wrapped food and the HFDC is designed for holding wrapped or boxed food.

Hot Food Display Case (HFD)



Combo Serve Hot Food Display Case (HFDC)



* Unwrapped food pictured in HFDC for display purposes only.

IMPULSE SERIES

Hot Food Display Cases

HFD & COMBO SPECIFICATIONS

Hot Food & Combo Serve Hot Food Display Case		
Hot Food Display Name	HFD	Combo Serve HFD
Model Number	HFDXXXXXX	HFDCXXXXX
Approx. Internal Volume	6 ft ³ (170 liters)	6 ft ³ (170 liters)
External Dimensions	Height	27.6" (700mm)
	Width	35.3" (896mm)
	Depth	19.7" (500mm)
Approx. Weight	154 lb (70kg)	160 lb (73kg)
Temp. Controlled Hot Plates	(6) 141W	(6) 141W
Lamps (heating & illumination)	(6) 40W Xenon	(6) 40W Xenon
Controller (adjustable temp.)	6 temperature controls, 100°F - 255°F	
Timers	12 Timers, programmable 30 min. to 4 hrs. (in 30 min. increments)	
Dual Circulation Fans	Standard on Model 5 and 7 only	Standard
Glass	ANSI Standard Z97.1 Tempered	
Power	115VAC 60Hz	115VAC 60Hz
Amp Rating	9.2 Amps	9.2 Amps
Standard Accessories	(4) Anodized 14" Pizza Pans (16) Stainless Steel Food Pans	(6) Removable Wire Racks
Optional Accessories	4" Leg Kit	4" Leg Kit
Safety Approvals: UL 197, CSA C22.2 No. 109-M81	UL File #E314888	UL File #E314888
Sanitation Approval: NSF/ANSI 4	UL File #E314888 (for HFD000001, 2, 3) NSF Listing D052450 (HFDXXXXXX)	NSF Listing D052450

NOTE: The manufacturer reserves the right to make product improvements and change specifications without notice.